

PROFESSIONAL XT

WOOD - PRODUCT DATASHEET 2020



TECHNICAL DATA (EN 13489)		
Reaction to fire	EN 13501	Cfl-s1
Emission of formaldehyde	EN 14342	E1
Brinell hardness (average value) Oak	(BHN) EN1534	3,7
Taber Abraser/Lacquer's wear resistance Protoco Natura <i>These typical values are not applicable for stained, brushed or hardwax oiled products.</i>	EN 13696	N/A
Reduction of sound weighted index ΔL_w in dB with 2 mm Tarkofoam/flex II	NF EN ISO 140-8 / Acc to NF EN ISO 717-2	17
Thermal insulation value (RT m ² K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,101 0,121 0,141
Thermal conductivity (W/m K)	EN 12664 / EN 14342:2013	0,104
Construction	3-layer with softwood core	

INSTALLATION	
Installation method	Floating or glue down
Installation instruction	Download from www.tarkett.com Contact your supplier for more details
Underfloor heating compatible	Maximum floor surface temperature 27°C with self-regulating under-floor heat system.
Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m ²	

RECOMMENDED ACCESSORIES	
Installation	Tarkofoam II / Tarkoflex II Installation kit
Aesthetics	Skirting, Pipe covers Transition moulding
Care & Maintenance	Wood Floor Care Kit / Spray Mop Kit Bioclean, Refresher
See more alternatives and the complete range of accessories @ www.tarkett.com	

DIMENSIONS & PACKAGE	10x190x1850
Thickness EN 13489 (mm)	10
Width (mm)	190
Length (mm)	1850
Wear layer thickness (mm)	2,5
Boards/pack	8
m ² /pack	2,81
m ² /pallet	98,42
Net weight/m ² (kg)	5,4
Due to the nature of the material this table shows typical values.	

MAINTENANCE
Tarkett wooden floors have a Protoco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details, such as saw marks. Please always refer to maintenance guidance available on websites.
See maintenance instructions @ www.tarkett.com

Professional XT
Protoco Natura



PROFESSIONAL XT

WOOD - PRODUCT DATASHEET 2020

DESIGN


Real wooden floors for special applications.

PRODUCT DATA	Material code	Dimensions L x W x H (mm)	Pattern	Surface treatment	Surface effect	Bevel (2 side)	Stained	Latin name	DoP no.
Oak Nature Authentic	41023001	1 850 x 190 x 10	1-strip	Proteco Natura	Brushed	Minibevel	Yes	1	0190-0102
Oak Rustic Authentic	41023002	1 850 x 190 x 10	1-strip	Proteco Natura	Brushed	Minibevel	Yes	1	0190-0102
Oak Rustic Soft Beige	41023005	1 850 x 190 x 10	1-strip	Proteco Natura	Brushed	Minibevel	Yes	1	0190-0102
Oak Nature	41023003	1 850 x 190 x 10	1-strip	Proteco Natura	Brushed	Minibevel	No	1	0190-0102
Oak Rustic	41023004	1 850 x 190 x 10	1-strip	Proteco Natura	Brushed	Minibevel	No	1	0190-0102
Oak Praline	41023006	1 850 x 190 x 10	1-strip	Proteco Natura	Brushed	Minibevel	Yes	1	0190-0102

1: Quercus Robur & Quercus Petraea



Oak Nature Authentic




Oak Rustic Authentic



Oak Rustic Soft Beige



Oak Nature



Oak Rustic



Oak Praline

The pictures only present the colour of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com. Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks. When sanding a wooden floor the appearance will change in colour, texture and surface effects.

For further and latest information please visit www.tarkett.com