


7 MM - CLASS 31 - AC3

THICKNESS	mm	7	EN 13329+A1
WIDTH	mm	197	EN 13329+A1
LENGHT	mm	1205	EN 13329+A1
SURFACE		Authentic	
EUROPEAN STANDARD	-		EN13329
PACKAGE THE DETAILS			
PIECE	12 piece / 1 package		
M ²	2,849 m ²		
KG	17 kg		
PALLET THE DETAILS			
PIECE	60 package / 1 pallet		
M ²	170,94 m ²		
KG	1060 kg		
CLASS	-	31	EN 13329+A1
ABRASION RESISTANCE	-	AC3	EN 13329+A1
THICKNESS SWELLING	%	≤18	ISO 24336
RESISTANCE TO IMPACT	SMALL BALL	N	≥8
	LARGE BALL	mm	≥500
WARRANTY DOMESTIC / COMMERCIAL	Years	10/5	-
RESISTANCE TO STAINING	-	Min. 5 (group 1 and 2) Min. 4 (group 3)	EN 438
SURCAFE SOUNDNESS	N/mm ²	≥1.0	EN 13329+A1
LOCK STRENGTH	LENGHT	kN/m	-
	WIDTH	kN/m	-
EFFECT OF A CASTOR CHAIR	25.000 Cycles	No Damage	EN 425:2002
EFFECT OF A FURNITURE LEG	-	No Damage	EN 424
OPENING BETWEEN ELEMENTS	mm	≤0,20	EN 13329+A1
HEIGHT DIFFIRENCE BETWEEN ELEMENTS	mm	≤0,15	EN 13329+A1
MOISTURE CONTENT	%	4-10	EN 322
FIRE RESISTANCE	Class	C _{fl} S1	EN 9239-1
FORMALDEHYDE EMISSION	mg/m ² h	≤3,5 (E1)	EN 12460-3



The mark of responsible forestry



Our products can also be produced with FSC and CARB certification upon request.