


TECHNICAL DATA SHEET
ELITE XL
12 MM - CLASS 33 - AC5

THICKNESS	mm	12	EN 13329+A1
WIDTH	mm	195	EN 13329+A1
LENGHT	mm	1202	EN 13329+A1
SURFACE		Country - Vintage	
EUROPEAN STANDARD	-		EN 13329
PACKAGE DETAILS			
PIECE	8 piece / 1 package		
M ²	1,87 m ²		
KG	20,5 kg		
PALLET DETAILS			
PIECE	50 package / 1 pallet		
M ²	93,5 m ²		
KG	1030 kg		
CLASS	-	33	EN 13329+A1
ABRASION RESISTANCE	-	AC5	EN 13329+A1
THICKNESS SWELLING	%	≤15	ISO 24336
RESISTANCE TO IMPACT	SMALL BALL	N	≥15
	LARGE BALL	mm	≥1000
WARRANTY DOMESTIC / COMMERCIAL	Years	25/15	-
RESISTANCE TO STAINING	-	Min. 5 (group 1 and 2) Min. 4 (group 3)	EN 438-2_5
SURFACE SOUNDNESS	N/mm ²	≥1.25	EN 13329+A1
LOCK STRENGTH	LENGHT	kN/m	f _{l0,2} ≥ 1
	WIDTH	kN/m	f _{s0,2} ≥ 2
EFFECT OF A CASTOR CHAIR	25.000 Cycles	No Damage	EN 425:2002
EFFECT OF A FURNITURE LEG	-	No Damage	EN 424
OPENING BETWEEN ELEMENTS	mm	≤0,20	EN 13329+A1
HEIGHT DIFFERENCE BETWEEN ELEMENTS	mm	≤0,15	EN 13329+A1
MOISTURE CONTENT	%	4-10	EN 322
FIRE RESISTANCE	Class	C _f S1	EN 9239-1
FORMALDEHYDE RELEASE	mg/m ² h	≤3,5 (E1)	EN 12460-3
SLIP RESISTANCE	Class	DS	EN 13893:2003
IMPACT SOUND REDUCTION	dB	15	EN ISO 10140-3
THERMAL RESISTANCE	(m ² K)/W	0,08	EN 12667:2001



Our products can also be produced with FSC® and CARB certification upon request.